

# CS-S1C-24WFBS



## Introduction

S1C action camera supports 1440P/30fps video recording, 8MP resolution photos, as high as 15 photos/s burst mode and time lapse mode of 5 minutes intervals.

Besides, in S1C there're 2 inch touchable screen and super aspheric lens. Our innovative distortion correction technology is used to ensure a pleasant experience during video recording.

## Key Features

|  |
|--|
| 1440P 30FPS Video With HDR             |
| OV Image Sensor WDR(3x)                |
| Built-In Touchable LCD Screen (2 inch) |
| Auto Low Light and Long Exposure       |
| Build In Wi-Fi and BLE 4.0(Broadcom)   |
| Support Micro SD card, up to 128GB     |
| Waterproof housing 40m                 |
| Distortion Correction                  |
| New Ambarella Video Processor A12      |



## Dimensions



---

## OPTIONAL COLOR

---

BLUE



GREY



YELLOW



ORANGE



# SPECIFICATION

|              |   |  |                            |          |               |
|--------------|---|--|----------------------------|----------|---------------|
| Video        | Video Format                                      | Resolution   | NTSC(fps)                  | PAL(fps) | Field Of View |
|              |   | 1080P  | 30                         | 25       | Wide          |
|              |   | 720P   | 30/60                      | 25/50    | Wide          |
|              |   | H.264 BP/MP/HP Level 5.1 With MP4 Mixed File Format  |                            |          |               |
|              | Record Mode                                       | Video<br>Video+Photo   |                            |          |               |
|              | Low Light   | Auto Adjust Frame Rate for enough exposure time purpose  |                            |          |               |
|              | Distortion Correct                                | Better X/Y Correct   |                            |          |               |
|              | HiLight Tag                                       | High Light Important Time point, used for Post processing  |                            |          |               |
|              | Loop Mode   | To set up the storage mode according to the time interval set  |                            |          |               |
|              | Meter Mode  | Center、Average、Spot  |                            |          |               |
| Professional | White Balance、ISO、Sharpness、Ev Comp、Color Pattern |  |                            |          |               |
| Single       | Photo Size  | 8MP Wide<br>4MP Wide<br>2MP Wide   |                            |          |               |
|              | Distortion Correct                                | Better X/Y Correct   |                            |          |               |
|              | Meter Mode  | Center、Average、Spot  |                            |          |               |
|              | Professional                                      | White Balance、ISO、Sharpness、Ev Comp、Color Pattern  |                            |          |               |
| Burst        | Photo Size  | 8MP wide<br>4MP Wide<br>2MP Wide   |                            |          |               |
|              | Burst Rate  | 15 pictures 1 second/15 pictures 2 seconds/15 pictures 3 second<br>10 pictures 1 seconds/10 pictures 2 second/10 pictures 3 second<br>5 pictures 1 second (default) /3 pictures 1 second |                            |          |               |
|              | Distortion Correct                                | Better X/Y Correct   |                            |          |               |
|              | Meter Mode  | Center、Average、Spot  |                            |          |               |
|              | Professional                                      | White Balance、ISO、Sharpness、Ev Comp、Color Pattern  |                            |          |               |
| Timelapse    | Shutter Mode                                      | Timelapse Photo、Timelapse Video  |                            |          |               |
|              | Photo Size  | 8MP Wide/4MP Wide/2MP Wide   |                            |          |               |
|              | Video Resolution                                  | 1080P/720P   |                            |          |               |
|              | Shutter Interval                                  | Timelapse Photo  | 1s、3s、5s、10s、30s、60s、300s  |          |               |
|              |   | Timelapse Video  | 0.5s、1s、1.5s、2s、2.5s、3s、5s |          |               |
|              | Meter Mode  | Center、Average、Spot  |                            |          |               |
|              | Distortion Correct                                | Better X/Y Correct   |                            |          |               |
| Professional | White Balance、ISO、Sharpness、Ev Comp、Color Pattern |  |                            |          |               |

|   |  |   |                                      |
|---|--|---|--------------------------------------|
| Playback                                | Decode Photo and Video Files in sd Card and Display it via LCD or HDTV   |   |                                      |
| Setup                                   | View   | Up、Down、Auto  |                                      |
|   | Default Mode   | Video、Single、Burst、Timelapse  |                                      |
|   | Driving Mode   | The camera automatically starts and Shutter after the camera detects the motion   |                                      |
|   | Vout Mode  | Switching HDMI HD output and AV analog output   |                                      |
|   | LED  | Set it on or off  |                                      |
|   | OSD  | Turn on screen display on or off  |                                      |
|   | Quickly Capture  | Camera will Fastest speed boot and start shutter  |                                      |
|   | Auto Off   | Set Auto Power Off Time   |                                      |
|   | Date And Time  | Set Date And Time   |                                      |
|   | Mic Gain   | Set The Gain of Mic   |                                      |
|   | Speaker Gain   | Set The Gain of Speaker   |                                      |
|   | Camera Reset   | Reset Camera to default Settings  |                                      |
| Wireless                                | BLE 4.0  | Embedded bluetooth4.0   |                                      |
|   | WIFI   | 802.11b/g/n、 Mobile App Support   |                                      |
|   |  | SSID  | Support SSID Modify with Mobile App  |
|   |  | KEY   | Support KEY Modify with Mobile App   |
|   |  | RESET   | Reset SSID and KEY to system default |
| Display                                 | HDMI   | Display With  |                                      |
|   | AV   | AV output Use USB Interface   |                                      |
|   | Embedded LCD   | LCD With Touch Pannel   |                                      |
| Lens Specification                      | 1/3" CMOS<br>Full glass lens for high image quality, 3mm@f3.0 140°Ultra-wide angle of view with less distortion  |   |                                      |
| Platform                                | Ambarella new generation Video Processor A12, using advanced 28-nm silicon technology  |   |                                      |
| Memory                                  | 2Gb DDR3、1Gb Nand Flash  |   |                                      |
| Sensor                                  | OV new generation Video Sensor OV4685  |   |                                      |
| Battery                                 | Battery Type   | Replaceable、Rechargeable li-ion battery   |                                      |
|   | Battery Parameters   | 1160mAh   |                                      |
|   | Battery Life   | 2 hours (Varies with different video mode)  |                                      |
| Audio                                   | 48kHz (sampling), AAC compression<br>Advanced AGC (automatic gain control)<br>Build-in two microphone for wind noise reduce<br>Single track/Beeps for shutter notify |   |                                      |
| Interface                               | Micro USB  | For charging when connect with power cable;<br>For playback/file transportation/charging when connecting with PC;<br>AV output                      |                                      |
|   | Micro HDMI   | For play on HDTV via HDMI cable   |                                      |
|   | MicroSD  | Storage card  |                                      |
| Storage                                 | Standard   | Class 10 or up to UHS-1 level Micro SD storage card   |                                      |
|   | Capacity   | 4GB、8GB、16GB、32GB、64GB、128GB  |                                      |
|   | Recording Time   | Varies with different resolution and frame rate   |                                      |
| Photo/Video Preview/<br>Playback /Setup | App for Mobile<br>Device   | For iOS and Android system<br>Live view, playback, recording, configuration, video file editing, and one-touch share to social media are supported. |                                      |
| Protection Grade                        | Camera   | 40 meters diving with waterproof case   |                                      |
|   | Remote   | IP66  |                                      |
| Operating Conditions                    | Temperature: -20° C to 45° C;  |   |                                      |
| Dimensions                              | 58mm(W)×45mm(H)×20.6(W)  |   |                                      |
| Weight                                  | About 99.7g  |   |                                      |