

RattlerV² 384

THERMAL IMAGING RIFLE SCOPE

The NEW RattlerV² is one of the most highly-anticipated product releases. Improving on what is already considered the best-selling thermal riflescope product family in the United States, the RattlerV² brings many of the most sought after design improvements into one sleek new housing. These improvements include, but are not limited to: dramatically expanded battery life offered through the unit's proprietary removable and rechargeable battery system, which will afford users up to 11 hours on a single charge (2 included), an expanded built-in reticle assortment, expanded brightness and contrast settings, shot activated recording with sound and new 12-micron thermal sensor that have the highest rated sensitivity rating (sub-20 mk) on the market. For a product family which was already boasted one of the best value propositions in the market, the NEW RattlerV²'s will only expand on that reputation.

The RattlerV² 25-384 with a 25mm Germanium lens and RattlerV² 35-384 with 35mm lens are the perfect addition to any hunter's arsenal. Equipped with a 384x288 resolution thermal sensor, these units have 2X or 3X magnification, and a detection range of 1200 or 1800 yards, respectively. This low base magnification allows for a wide field of view, which many hog hunters prefer, as it allows them to see and track multiple animals in a group at once.

- Superior sub-20 milikelvin thermal sensitivity
- 384x288 resolution with 12-micron sensor
- Fast 50Hz imaging
- High resolution OLED display
- Adjustable color palettes
- Various reticle types and colors
- 1x, 2x, 4x, 8x digital zoom
- On-board video/audio recording and image capture
- Built-in EMMC storage (16 GB)
- Shot Activated Recording (SAR)
- Wi-Fi data transmission
- Stadiametric rangefinder
- Standby mode
- Up to 11 hours battery life
- External power supply compatibility
- Waterproof & shockproof
- 3-year warranty



SPECIFICATIONS

	RattlerV ² 25-384	RattlerV ² 35-384
Detector	12µm VOx Uncooled Focal Plane Array	12µm VOx Uncooled Focal Plane Array
Resolution	384 x 288	384 x 288
NETD	Less than 20 mK (25°C, F# = 1.0)	Less than 20 mK (25°C, F# = 1.0)
Refresh Rate	50 Hz	50 Hz
Lens System	25 mm; F/1.0	35 mm; F/1.0
Magnification	2x - 16x	3x - 24x
Field of View	10.5° x 7.9°	7.5° x 5.6°
Dioptr Adjustment	-5 to +5 diopters	-5 to +5 diopters
Focus Range	0.5 m to infinity	2 m to infinity
Exit Pupil	6 mm	6 mm
Eye Relief	45 mm	45 mm
Digital Zoom	1x, 2x, 4x, 8x	1x, 2x, 4x, 8x
Detection Range (6' object)	1200 m/yd	1800 m/yd
Display	0.39-inch, OLED, 1024x768	0.39-inch, OLED, 1024x768
Palettes	Black hot, White hot, Red hot, Fusion	Black hot, White hot, Red hot, Fusion
Flat Field Correction	Auto, Manual, External Correction	Auto, Manual, External Correction
Scene Mode	Cold, Warm	Cold, Warm
Boresight Adjustment	Digital Controlled	Digital Controlled
Video/Audio Recording	Yes	Yes
Image Capture	Yes	Yes
Standby Mode	Yes	Yes
Storage	Built-in EMMC (16 GB)	Built-in EMMC (16 GB)
PIP	Yes	Yes
Defective Pixel Correction	Yes	Yes
WiFi Hotspot	Yes	Yes
Hot Track	Yes	Yes
Reticle	10 types, 4 colors, on/off	10 types, 4 colors, on/off
Distance Measurement	Yes (Stadiametric)	Yes (Stadiametric)
Shot Activated Recording (SAR)	Yes	Yes
Battery Type	Replaceable and Rechargeable Li-ion Battery	Replaceable and Rechargeable Li-ion Battery
Battery Life (Operating, 20°C)	Up to 11 hours (25°C, with hotspot off)	Up to 11 hours (25°C, with hotspot off)
External Power Supply	5 VDC, 2 A, USB Type-C	5 VDC, 2 A, USB Type-C
Operating Temperature Range	-30°C to +55°C (-22°F to 131°F)	-30°C to +55°C (-22°F to 131°F)
Protection Level	IP67	IP67
Max. Recoil	1000 g/0.4 ms	1000 g/0.4 ms
Weight (w/o mount and battery)	0.49 kg (1.08 lb)	0.51 kg (1.13 lb)
Dimensions (w/o mount)	219 x 68 x 67 mm (8.5 x 2.7 x 2.6 in)	221 x 68 x 67 mm (8.7 x 2.7 x 2.6 in)
Package Includes	Thermal Imaging Rifle Scope, Mount, Two Rechargeable Battery, Charger, USB Cable, Lens Cloth, Manual, Carrying Case	Thermal Imaging Rifle Scope, Mount, Two Rechargeable Battery, Charger, USB Cable, Lens Cloth, Manual, Carrying Case

Specifications are subject to change without notice.



MAIN OFFICE | 173 West Main Street | PO Box 962 | Springerville, AZ 85938, USA
Tel. +1.928.333.4300 | info@agmglobalvision.com | www.agmglobalvision.com

EUROPEAN OFFICE | #6 Andrey Lyapchev Blvd | Sofia, P.C. 1756 | Bulgaria
Tel. +35.988.560.0326 | info@agmglobalvision.eu | www.agmglobalvision.eu

www.agmglobalvision.com